# Golden Compound PP S<sup>2</sup>PC 5045 BO

### Polypropylene

#### Golden Compound GmbH

#### Message:

Easy flowing PP compound with 50 wt% natural fibers derived from Sunflower Seed Hulls.

Fibers derived from Sunflower Seed Hulls are a side product of Sunflower Oil production. They are GMO free, do not compete with the food chain and do not require additional areal. S<sup>2</sup> PC has a lower carbon footprint than the materials it is targeted to replace.

General Information			
Filler / Reinforcement	Natural Fiber,50% Filler by Weight		
Features	Good Flow		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.09	g/cm³	ISO 1183
Melt Volume-Flow Rate (MVR) (190°C/5.0 kg)	24.0	cm³/10min	ISO 1133
Molding Shrinkage			ISO 294-4
Across Flow	1.0	%	
Flow	0.80	%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	3000	MPa	ISO 527-2
Tensile Stress	29.0	MPa	ISO 527-2
Tensile Strain (Break)	2.0	%	ISO 527-2
Flexural Modulus	2900	MPa	ISO 178
Flexural Stress	45.0	MPa	ISO 178
Flexural Strain	2.7	%	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	2.0	kJ/m²	ISO 179/1eA
Charpy Unnotched Impact Strength (23°C)	10	kJ/m²	ISO 179/1eU
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature			
0.45 MPa, Unannealed	140	°C	ISO 75-2/B
1.8 MPa, Unannealed	95.0	°C	ISO 75-2/A
Vicat Softening Temperature	100	°C	ISO 306/B
Injection	Nominal Value	Unit	
Drying Temperature	80.0	°C	
Drying Time	4.0	hr	
Suggested Max Moisture	< 0.040	%	
Processing (Melt) Temp	< 190	°C	
Mold Temperature	20.0	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

