LightSpan® LS-3252

Silicone

NuSil Technology

Message:

From LEDs to fiber optics, NuSil Technology's LightSpan[™] brand product line delivers the most comprehensive line of refractive index matching adhesives, encapsulants and thermosets available. The benefits of silicone include the following: Thermal Stability Low lonic Species Maintain Optical Clarity (90% minimum @ 400nm) Low Moisture Absorption (<0.4%) Optimization for UV Resistance Adjustable Cure Low Outgassing Low Shrinkage, <1% Low Modulus: Stress reduction for bonding materials with different coefficients of thermal expansion Gernal Purpose: Optical Gels Comments: Low Viscosity and 1.52 RJ, Index Matches BK7, GlassUse with Phosphor, Index matches to plastic such as COC

General Information						
Features	Good Thermal Stability Good UV Resistance					
			Low Moisture Absorption Low Shrinkage Low to No Outgassing			
		Low Viscosity				
	Forms	Gel				
Processing Method	Encapsulating					
Optical	Nominal Value					
Refractive Index	1.520					
Thermoset	Nominal Value	Unit				
Thermoset Components						
Part A	Mix Ratio by Weight: 1.0					
Part B	Mix Ratio by Weight: 1.0					
Uncured Properties	Nominal Value	Unit				
Viscosity	0.43	Pa·s				
Curing Time (150°C)	0.50	hr				
Pot Life	360	min				
Cured Properties	Nominal Value	Unit				
Shore Hardness						
Shore OO	10					
Shore OOO	65					

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

