S&E; Wire & Cable GTPO9005

Thermoplastic Polyolefin Elastomer

S&E; Specialty Polymers, LLC

Message:

A proprietary, low gravity, non-halogen based flame retardant thermoplastic polyolefin designed for extrusion in wire and cable applications.

General Information			
Features	Flame Retardant		
	Halogen Free		
	Low Density		
Uses	Wire & Cable Applications		
Forms	Pellets		
Processing Method	Wire & Cable Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.05	g/cm³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	9.65	MPa	ASTM D638
Tensile Elongation (Break)	400	%	ASTM D638
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	34	%	ASTM D2863

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

