

AXLENE® 35

Polypropylene Homopolymer

INDELPRO, S.A. de C.V.

Message:

AXLENE35 is a homopolymer of propylene for general purposes; AXLENE35 is designed for injection machines and can be used in thin wall articles. The base resin in this product meets the requirements of the US Food and Drug Administration (FDA) contained in the Code of Federal Regulations in 21 CFR 177.1520.

Features:

High rigidity

Good process stability

Good dimensional stability

Typical Applications:

General injection

Housewares

Containers

Thin wall articles

General Information			
Features	Good dimensional stability Rigidity, high Homopolymer Good processing stability		
Uses	Thin wall parts Household goods Container General		
Agency Ratings	FDA 21 CFR 177.1520		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.900	g/cm ³	ASTM D792A
Melt Mass-Flow Rate (MFR)	35	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	35.0	MPa	ASTM D638
Tensile Elongation (Yield)	9.0	%	ASTM D638
Flexural Modulus	1390	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	26	J/m	ASTM D256A
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	115	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

