

# Magnobond 8005

Epoxy; Epoxide

Magnolia Plastics, Inc.

## Message:

Magnobond 8005 is an Epoxy; Epoxide (Epoxy) product filled with silver. It is available in North America. Typical application: Adhesives/Tapes.

Characteristics include:

Conductive

Good Adhesion

Low Moisture Absorption

Low Shrinkage

General Information			
Filler / Reinforcement	Silver		
Features	Electrically Conductive		
	Good Adhesion		
	Low Moisture Absorption		
	Low Shrinkage		
Uses	Adhesives		
Appearance	Silver		
Forms	Paste		
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	5.0E-4	ohms · cm	ASTM D257
Thermoset	Nominal Value	Unit	
Thermoset Components			
Hardener	Mix Ratio by Weight: 57		
Resin	Mix Ratio by Weight: 100		
Pot Life (25°C)	240	min	
Shelf Life (4°C)	26	wk	
Demold Time			
24°C	1400	min	
99°C	30	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT