

Kumho KTR KTR-401H

Styrene Butadiene Styrene Block Copolymer

Korea Kumho Petrochemical Co., Ltd.

Message:

KUMHO KTR ® 401H polymer is a radial block copolymer based on styrene and butadiene with bound styrene of 32.5% mass. It is supplied in two physical forms, identified as follows in the grade nomenclature:

KTR 401H supplied as porous pellets

KTR 401HP supplied as powder

General Information		
Forms	Pellets	
Physical	Nominal Value	Unit
Specific Gravity	0.938	g/cm ³
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	< 1.0	g/10 min
Ash Content	0.1	wt%
Oil Content	0.0	wt%
Solution Viscosity ¹ (25°C)	22	mPa · s
Styrene Content	32.5	wt%
Volatile Matter	0.50	wt%
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A, 5 sec)	87	
Elastomers	Nominal Value	Unit
Tensile Stress (300% Strain)	3.33	MPa
Tensile Strength (Break)	27.5	MPa
Tensile Elongation (Break)	710	%
NOTE		
1.	5.23 wt% in toluene	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT