

Alpha PVC GEX 03-040 F NATURAL

Flexible Polyvinyl Chloride

AlphaGary

Message:

LOW COST COMPOUND FOR WINDOW LACE, NOT RECOMMENDED FOR OEM.

General Information			
RoHS Compliance	Contact Manufacturer		
Appearance	Natural Color		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.36 to 1.40	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	77 to 87		
Shore A, 15 sec	70 to 80		
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (1.91 mm)	13.1	MPa	ASTM D412
Tensile Elongation (Break, 1.91 mm)	300	%	ASTM D412

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

