

Amilan® CM6241M

Polyamide Copolymer

Toray Resin Company

Message:

Amilan® CM6241M is a Polyamide Copolymer (Nylon Copolymer) product. It is available in Asia Pacific, Europe, or North America. Primary characteristic: good flexibility.

General Information			
Features	Good Flexibility		
Part Marking Code	>PA<		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	1.14	g/cm ³	ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (23°C)	65.0	MPa	ISO 527-2
Tensile Strain (Break, 23°C)	50	%	ISO 527-2
Flexural Modulus (23°C)	2200	MPa	ISO 178
Flexural Stress (23°C)	90.0	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	6.0	kJ/m ²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	190	°C	DSC
Fill Analysis	Nominal Value	Unit	
Melt Viscosity ¹			
230°C	1260	Pa·s	
250°C	750	Pa·s	
NOTE			

1. Koka Type Flow Tester

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT