Braskem PP H 510

Polypropylene Homopolymer

Braskem

Message:

Description:

H 510 is a low melt flow rate homopolymer, specially designed for biorented filmes (BOPP) in tenter frame lines. This product features high transparency and gloss, good mechanical strenght, high stiffness, high toughness and excellent processability. Applications:

Adhesive tapes; Food and textile packaging; Films for conversion process.

General Information			
Features	Good Processability		
	Good Toughness		
	High Gloss		
	High Stiffness		
	Homopolymer		
Uses	Adhesives		
	Film		
	Food Packaging		
	Таре		
	Textile Applications		
Agency Ratings	FDA 21 CFR 177.1520		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.905	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	2.6	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale, Injection Molded)	96		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield, Injection Molded)	34.0	MPa	ASTM D638
Tensile Elongation (Yield, Injection			
Molded)	13	%	ASTM D638
Flexural Modulus - 1% Secant (Injection Molded)	1200	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, Injection Molded)	40	J/m	ASTM D256

Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			ASTM D648
0.45 MPa, Unannealed, Injection Molded	96.0	°C	
1.8 MPa, Unannealed, Injection Molded	53.0	°C	
Vicat Softening Temperature	157	°C	ASTM D1525 ¹
NOTE			
1.	Loading 1 (10 N)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

