

Viton® VTR-9209

Fluoroelastomer

DuPont Performance Elastomers

Message:

Viton®VTR-9209 is a fluororubber (Fluorelastomer) product. It can be processed by extrusion and is available in North America or Europe. Viton®VTR-9209 application areas include engineering/industrial accessories, sealing applications, hoses and coating applications. The main characteristics are: chemical resistance.

General Information			
Features	Solvent resistance		
	Fuel resistance		
Uses	Washer		
	Pipe		
	Seals		
	Coating application		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.86	g/cm ³	ASTM D792
Elastomers	Nominal Value	Unit	Test Method
Compression Set (200°C, 70 hr)	33	%	ASTM D395
Additional Information			

Nominal Viscosity, ML 1 + 10, 121°C: 30Polymer Fluorine Content: 69.1%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

