CGPC PVC H-80

Polyvinyl Chloride

China General Plastics Corporation

Message:

CGPC PVC H-80 is a Polyvinyl Chloride material. It is available in Asia Pacific or North America. Primary attribute of CGPC PVC H-80: Impact Resistant. Typical applications include:

Consumer Goods

Film

Furniture

Sheet

Wire & Cable

General Information			
Features	High Impact Resistance		
Uses	Film		
	Footwear		
	Furniture		
	Sheet		
	Wire & Cable Applications		

Physical	Nominal Value	Unit	Test Method
Apparent Density	0.46 to 0.52	g/cm³	ISO 60
K-Value	79.0 to 81.0		ISO 1628-2
Particle Size - 45 Mesh Pass ¹	> 99.0	%	
Degree of Polymerization	1700 to 1900		
Residual Vinyl Chloride Monomer	< 1	ppm	ISO 6401
Volatiles	< 0.30	%	ISO 1269
NOTE			
1	U. CDA 150		

1. Honeywell SRA-150

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

