

Manner Flexible PVC M6112

Flexible Polyvinyl Chloride

Manner Plastics, L.P.

Message:

Recommended Applications: 80°C General Purpose Injection Molding Compound for Appliance and Automotive Harness Components. This product complies with the European Union Restriction on Hazardous Substances (RoHS) directive. Complies with Ford Motor Co. Specification ESB-M4D317A Type II and meets Chrysler Corporation Specification MC-DC225.

General Information			
Features	General Purpose		
Uses	Appliance Components		
	Automotive Applications		
	General Purpose		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.24 to 1.28	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	52 to 58		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	8.27	MPa	ASTM D638
Tensile Elongation (Break)	450	%	ASTM D638
Additional Information	Nominal Value	Unit	
Stock Temperature - Recommended Molding	160	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

