

Fainplast PVC RKI 01298/W-UV

Rigid Polyvinyl Chloride

Fainplast Compounds S.r.l

Message:

Fainplast PVC RKI 01298/W-UV is a Rigid Polyvinyl Chloride product. It can be processed by injection molding and is available in Africa & Middle East, Europe, Latin America, or North America.

General Information			
Features	Low (to None) Lead Content		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.44 to 1.48	g/cm ³	ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			ISO 527-2
Yield	> 41.0	MPa	
Break	> 39.0	MPa	
Tensile Strain (Break)	> 100	%	ISO 527-2
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (23°C)	140 to 160	J/m	ISO 180

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

