

NEOFLON™ EP-541

Ethylene Tetrafluoroethylene Copolymer

DAIKIN AMERICA, INC.

Message:

NEOFLON ETFE is a copolymer of tetrafluoroethylene and ethylene, and has the lowest specific gravity among all fluoropolymers. It has superior characteristics in melt processability and mechanical properties compared with PTFE and FEP, and has good electrical and chemical properties. It is suitable for applications requiring its mechanical toughness, chemical resistance, heat resistance and electrical properties.

Features

Superior to EP-521 in stress crack resistance. Suitable for thick-walled wire coating and extrusion molded articles.

General Information		
Features	Copolymer	
	Good electrical performance	
	Good chemical resistance	
	Good toughness	
Uses	Wire sheath	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Specific Gravity ¹	1.74	g/cm ³
Melt Mass-Flow Rate (MFR)	4.0 - 8.0	g/10 min
NOTE		
1.	25°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT