

Sylvin 5197-92 Green 3145

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:
Sylvin 5197-92 Green 3145 Is A Vinyl Compound Formulated For Grounding Wire Applications That Require Improved Slip.

| General Information | | | |
|--------------------------------------|---------------------------|-------------------|-------------|
| Additive | Slip | | |
| Features | Slip | | |
| Uses | Wire & Cable Applications | | |
| Appearance | Green | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.33 | g/cm ³ | ASTM D792 |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A, 10 sec) | 92 | | ASTM D2240 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength | 17.2 | MPa | ASTM D638 |
| Tensile Elongation (Break) | 350 | % | ASTM D638 |
| Thermal | Nominal Value | Unit | Test Method |
| Continuous Use Temperature | 105 | °C | ASTM D794 |
| Melting Temperature | 171 to 182 | °C | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT