

Softell TBP 237D NAT

Polyolefin
LyondellBasell Industries

Message:

Softell TBP 237D Nat is a high performance thermoplastic polyolefin, designed for use in applications where softness and elasticity is a key requirement. This product is in an experimental phase

General Information			
Features	Good Processability		
	High Elasticity		
	Soft		
Uses	Film		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	0.60	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	10.0	MPa	ASTM D638
Tensile Elongation (Break, Injection Molded)	800	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT