

# NEO-ZEX™ 1014T

Linear Low Density Polyethylene  
Prime Polymer Co., Ltd.

Message:

NEO-ZEX™ 1014T is a Linear Low Density Polyethylene product. It can be processed by injection molding and is available in Asia Pacific, Europe, or North America. Typical application: Consumer Goods. Primary characteristic: antioxidant.

General Information			
Additive	Antioxidant		
Features	Antioxidant		
	Soft		
Uses	Consumer Applications		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.910	g/cm³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	10	g/10 min	ISO 1133
Environmental Stress-Cracking Resistance	500	hr	ASTM D1693
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D)	49		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	7.10	MPa	ISO 527-2
Tensile Strain (Break)	> 300	%	ISO 527-2
Flexural Modulus	110	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength	No Break		ISO 179
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	80.0	°C	ISO 306
Melting Temperature	113	°C	ISO 11357-3

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT