Moplen RP5007K

Polypropylene Random Copolymer

PolyMirae

Message:

Moplen RP5007K is a nucleated and very high fluidity polypropylene random copolymer manufactured by PolyMirae using Spheripol process technology licensed from LyondellBasell.

Moplen RP5007K is specially designed for good processability and excellent clarity in low processing temperature with balanced mechanical properties. Moplen RP5007K is a random copolymer particularly suitable for injection molding of DVD case, houseware, thin walled articles (TWIM) for food and non food applications, transparency containers and boxes of big size.

Moplen RP5007K meets the FDA requirement in the code of Federal Regulations in 21 CFR 177.1520 for food contact.

Additive Nucleating Agent Features Food Contact Acceptable Good Processability	General Information			
Good ProcessabilityHigh ClarityHigh ClarityHigh FlowHigh GlossNucleatedRadom CopolymerVersionContainersHigh PloxKashold GoodsMetale PackagingXanon CopolymerPhysicalPhysicalPhysicalPhysicalPhysicalPhysicalNominal ValueQintinano GoodGondancesKight PackagingYangen Kathogen Kath	Additive	Nucleating Agent		
High ClarityHigh ClarityHigh FlowHigh FlowHigh GlossNucleatedRandom CopolymerVersionContainersHigh PokaciaMathed GloodsMedia PackagingVersionAgency RatingsFDA 21 CFR 177.1520PhysicaPhysicaPhysicaMomina ValueIndiTest MethodPonoQondoglondAgency Ratify Clorify Clorify75QindinaRathass-Flow Rate (MFR) Clorify Clorify93Test MethodRachwell Hardness (R-Scale)93GensinaChanina ValueNomina ValueNeinia ValueNationa State (MFR) Clorify Clorify11Agancy Rate (MFR) Clorify Clorify12MethaniaNomina ValueNationa State (Manone Clorify Clorify13Mathed Clorify Clorify14Manone Clorify Clorify15Mathed Clorify Clorify16Mathed Clorify Clorify17Mathed Clorify Clorify18Mathed Clorify Clorify19Mathed Clorify Clorify10Mathed Clorify Clorify10Mathed Clorify Clorify10Mathed Clorify Clorify10101112131414<	Features	Food Contact Acceptable		
High FlowHigh FlowHigh GlossNucleatedRandom CopolymerUsesContainersHousehold GoodsMedia PackagingPhysicalFDA 21 CFR 177.1520PhysicalNominal ValueUnitTest MethodDensity0.900gonoma Variant (MFR) (230°C/2.16)kg75gonoma Variant (MFR) (230°C/2.16)kg75gonoma Variant ValueUnitTest MethodRockwell Hardness (R-Scale)93		Good Processability		
High Gloss Nucleated Radom CopolymerUsesContainers Household Goods Media PackagingAgency RatingsFDA 21 CFR 177.1520PhysicalNominal ValueOnitinares Household Goods Media PackagingPhysicalNominal ValueOpolog/cm ² PhysicalNominal ValueDensity0.900Media PackagingMethodg/cm ² MethodSTM D1505Methodg/cm ² MethodNominal ValueMethodNominal ValueMethodNominal ValueMethodNominal ValueNominal ValueUnitRockwell Hardness (R-Scale)93Stor D705ASTM D785MechanicalNominal ValueNominal ValueUnitTensile Elongation (Yield)180InsoleMPaInsoleStor D638Insole IndotationNortholdInsole IndotationNortholdMethodulus180Northol ZuffordArtholdMethodulusNortholaInfordStor D626InfordStor D626MethodulusNortholaMethodulusStor D626MethodulusStor D626MethodulusStor D626MethodulusStor D626MethodulusStor D626MethodulusStor D626MethodulusStor D626MethodulusStor D626MethodulusStor D626MethodulusStor D626 <t< td=""><td></td><td>High Clarity</td><td></td><td></td></t<>		High Clarity		
Nucleated Radom CopolymerUsesContainers Household Goods Media PackagingAgeny RatingsFDA 21 CFR 177.1520PhysicalNominal ValueOninal ValueNoff0.900grom of Stat MethodBensty0.9000.900grom of Stat MethodMeth Mass-Flow Rate (MFR) (230°C/21)grom of Stat MethodMeth Mass-Flow Rate (MFR) (230°C/21)grom of Stat MethodMeth Mass-Flow Rate (MFR) (230°C/21)grom of Stat MethodMethods (Nachon Methodgrom of Stat MethodMethod Stat MethodNominal ValueMethod (Stat MethodNominal ValueMethod (Stat Method)Nominal ValueMethod (Stat Method)Stat MethodMethod (Stat Method)Nominal ValueMethod (Stat Method)Stat MethodMethod (Stat Method)Nominal ValueMethod (Stat Method)Nominal Value<		High Flow		
Random CopolymerUsesContainers Household Goods Media PackagingAgnorg AntonsFDA 1 CFR 177.1520PhysicalNominal ValueNominal ValueInitDensity0.900Met Mass-Flow Rate (MFR) (230°C/26)JSylJHardnessNominal ValueMet Mass-Flow Rate (MFR) (230°C/26)JSylJMet MathedIntMet MathedIntMet MathedJSylJMet MathedJMet MathedJMathed Int Cale (Mathed)JMet MathedJMathed Int Cale (Mathed)JMet MathedJMathed Int Cale (Mathed)JMet MathedJMathed Int Cale (Mathed)JMathed Int Cale (Mathed)<		High Gloss		
UsesContainers Household Goods Media PackagingAgency RatingsFDA 21 CFR 177.1520PhysicalNominal ValueUnitDensity0.900g/cm andMethadss-Flow Rate (MFR) (230°C/2.16) kg)75g/10 minMethadsserNominal ValueUnitMethadsser3Test MethodMethadsserNominal ValueUnitRockwell Hardness (R-Scale)93Test MethodMechanicalNominal ValueUnitTest MethodMechanicalNominal ValueUnitTest MethodTensile Etongation (Yield)11%ASTM D538Flexural Modulus1180MPaASTM D538ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D556ThermalNominal ValueUnitTest MethodNotched Izod Impact (23°C)61,0Sind D56Pherumaneed, Injection Modelow51,0Sind D56Pherumaneed, Ingection Modelow51,0Sind D56		Nucleated		
Household Goods Media PackagingAgency RatingsFDA 21 CFR 177.1520PhysicalNominal ValueUnitDensity0900g/cm³Meth Mass-Flow Rate (MFR) (230°C/2.16) g/0g/cm³ASTM D1505Meth Mass-Flow Rate (MFR) (230°C/2.16) g/075g/10 minASTM D1238RadnessNominal ValueUnitTest MethodRackwell Hardness (R-Scale)93InitTest MethodRockwell Hardness (R-Scale)93STM D783MechanicalNominal ValueUnitTest MethodTestie Storegth (Yield)294MPaASTM D638Testie Storegth (Yield)1180MPaASTM D638Insile Storegth (Yield)1180MPaASTM D638Insile Storegth (Yield)1180MPaASTM D638Insile Storegth (Yield)44JrinASTM D638Insile Storegth (Yield)44JrinASTM D636Insile Storegth (Yield)910Test MethodInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)910Minal ValueMinal ValueInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)810Mi		Random Copolymer		
Household Goods Media PackagingAgency RatingsFDA 21 CFR 177.1520PhysicalNominal ValueUnitDensity0900g/cm³Meth Mass-Flow Rate (MFR) (230°C/2.16) g/0g/cm³ASTM D1505Meth Mass-Flow Rate (MFR) (230°C/2.16) g/075g/10 minASTM D1238RadnessNominal ValueUnitTest MethodRackwell Hardness (R-Scale)93InitTest MethodRockwell Hardness (R-Scale)93STM D783MechanicalNominal ValueUnitTest MethodTestie Storegth (Yield)294MPaASTM D638Testie Storegth (Yield)1180MPaASTM D638Insile Storegth (Yield)1180MPaASTM D638Insile Storegth (Yield)1180MPaASTM D638Insile Storegth (Yield)44JrinASTM D638Insile Storegth (Yield)44JrinASTM D636Insile Storegth (Yield)910Test MethodInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)910Minal ValueMinal ValueInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)810Minal ValueMinal ValueInsile Storegth (Yield)810Mi				
Media PackagingAgency RatingsFDA 21 CFR 177.1520PhysicalNominal ValueUnitDensity0.900g.cm ³ Meth Mass-Flow Rate (MFR) (230°C/2.16) kg)75g.l0 minMeth Mass-Flow Rate (MFR) (230°C/2.16) kg)75g.l0 minMeth Mass-Flow Rate (MFR) (230°C/2.16) kg)Nominal ValueUnitRednessNominal ValueUnitRedness93Start D638MechanicalNominal ValueUnitMechanicalSaft D40MPaTensile Strength (Yield)294MPa11%10ASTM D638Flexual Modulus1180MPaIngaetNominal ValueUnitIngaetNominal ValueUnitIngaetMominal ValueUnitIngaetMominal ValueUnitIngaetMominal ValueUnitIngaetMominal ValueUnitIngaetMominal ValueUnitMethodJind ValueUnitDefection Temperature Under CastoffJinStretter CastoffJinScatoffMathodStretter CastoffStretter Castoff	Uses	Containers		
Agency RatingsFDA 21 CFR 177.1520PhysicalNominal ValueUnitTest MethodDensity0.900g/cm³ASTM D1505Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)75g/10 minASTM D1238HardnessNominal ValueUnitTest MethodRockwell Hardness (R-Scale)93STM D785MechanicalNominal ValueUnitTest MethodTensile Strength (Yield)29.4MPaASTM D638Flexural Modulus11%1ASTM D638Flexural Modulus1180MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256Peffection Temperature Under Load (0.45 MPA, Unannealed, Injection Molded)§1.0°cASTM D648		Household Goods		
PhysicalNominal ValueUnitTest MethodDensity0.900g/cm³ASTM D1505Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)75g/10 minASTM D1238HardnessNominal ValueUnitTest MethodRockwell Hardness (R-Scale)93.ASTM D785MechanicalNominal ValueUnitTest MethodTensile Strength (Yield)29.4MPaASTM D638Flexural Modulus11%ASTM D638Flexural Modulus1180MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 Ma, Unannealed, Injection Molded)§1.0°CASTM D648		Media Packaging		
PhysicalNominal ValueUnitTest MethodDensity0.900g/cm³ASTM D1505Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)75g/10 minASTM D1238HardnessNominal ValueUnitTest MethodRockwell Hardness (R-Scale)93.ASTM D785MechanicalNominal ValueUnitTest MethodTensile Strength (Yield)29.4MPaASTM D638Flexural Modulus11%ASTM D638Flexural Modulus1180MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 Ma, Unannealed, Injection Molded)§1.0°CASTM D648				
Density0.900g/cm³ASTM D1505Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)75g/10 minASTM D1238HardnessNominal ValueUnitTest MethodRockwell Hardness (R-Scale)93Test MethodTest MethodMechanicalNominal ValueUnitTest MethodTensile Strength (Yield)29.4MPaASTM D638Tensile Elongation (Yield)11%ASTM D638Flexural Modulus1180MPaASTM D638ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256Peffection Temperature Under Load (0.45 MPa, Unannealed, Injection Molded)j1.0°cContract Astm Defaj1.0°cASTM D648	Agency Ratings	FDA 21 CFR 177.1520		
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)75g/10 minASTM D1238HardnessNominal ValueUnitTest MethodRockwell Hardness (R-Scale)93JantonASTM D785MechanicalNominal ValueUnitTest MethodTensile Strength (Yield)29.4MPaASTM D638Tensile Elongation (Yield)11%ASTM D638Flexural Modulus1180MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodPeffection Temperature Under Load (0.45 Ha, Unannealed, Injection Molded)\$1.0°C	Physical	Nominal Value	Unit	Test Method
kg)75g/10 minASTM D1238HardnessNomial ValueUnitTest MethodRockwell Hardness (R-Scale)93Test MethodASTM D785MechanicalNominal ValueUnitTest MethodTensile Strength (Yield)29.4MPaASTM D638Tensile Elongation (Yield)11%ASTM D638Flexural Modulus1180MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45)51.0%ASTM D648	Density	0.900	g/cm³	ASTM D1505
HardnessNominal ValueUnitTest MethodRockwell Hardness (R-Scale)93ASTM D785MechanicalNominal ValueUnitTest MethodTensile Strength (Yield)29.4MPaASTM D638Tensile Elongation (Yield)11%ASTM D638Flexural Modulus1180MPaASTM D638ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 MPa, Unannealed, Injection Molded)91.0°C				
Rockwell Hardness (R-Scale)93ASTM D785MechanicalNominal ValueUnitTest MethodTensile Strength (Yield)29.4MPaASTM D638Tensile Elongation (Yield)11%ASTM D638Flexural Modulus1180MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 WPa, Unannealed, Injection Moled)91.0°c			-	
MechanicalNominal ValueUnitTest MethodTensile Strength (Yield)29.4MPaASTM D638Tensile Elongation (Yield)11%ASTM D638Flexural Modulus1180MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45) MPa, Unannealed, Injection Model91.0°CASTM D648			Unit	
Tensile Strength (Yield)29.4MPaASTM D638Tensile Elongation (Yield)11%ASTM D638Flexural Modulus1180MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 MPa, Unannealed, Injection Molded)91.0°C				
Tensile Elongation (Yield)11%ASTM D638Flexural Modulus1180MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 MPa, Unannealed, Injection Molded)91.0°C		Nominal Value	Unit	Test Method
Flexural Modulus1180MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 MPa, Unannealed, Injection Molded)91.0°CASTM D648	Tensile Strength (Yield)	29.4	MPa	ASTM D638
ImpactNominal ValueUnitTest MethodNotched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 MPa, Unannealed, Injection Molded)91.0°CASTM D648	Tensile Elongation (Yield)	11	%	ASTM D638
Notched Izod Impact (23°C)44J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 MPa, Unannealed, Injection Molded)91.0°CASTM D648	Flexural Modulus	1180	MPa	ASTM D790
ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 MPa, Unannealed, Injection Molded)91.0°CASTM D648	Impact	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed, Injection Molded) 91.0 °C ASTM D648	Notched Izod Impact (23°C)	44	J/m	ASTM D256
MPa, Unannealed, Injection Molded) 91.0 °C ASTM D648	Thermal	Nominal Value	Unit	Test Method
Optical Nominal Value Unit Test Method	-	91.0	°C	ASTM D648
	Optical	Nominal Value	Unit	Test Method

Haze

%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

