

Devcon Epoxy Concrete Sealer

Epoxy; Epoxide

Devcon

Message:

A 100% solids, two-component, self-leveling, non-voc clear epoxy sealer for sealing and water-proofing concrete, masonry, and wood surfaces

Intended Use:

Ideal clear coating high traffic areas. A good primer for damp surfaces before applying a top coat.

Product Features:

Resists industrial chemicals

Applies with brush or roller

Bonds to damp surfaces

Applies at temperatures as low as 40°F

General Information			
Features	Low VOC		
	Good chemical resistance		
Uses	Coating application		
Appearance	Clear/transparent		
Physical	Nominal Value	Unit	Test Method
Solid content-by Volume	100	%	
Temperature Resistance			
Dry	82	°C	
Wet	38	°C	
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	85		ASTM D2240
Thermoset	Nominal Value	Unit	
Thermoset Components			
	Mixing ratio by weight: 2.8		
Component a	Mixing ratio by capacity: 2.2		
	Mixing ratio by weight: 1.0		
Component B	Mixing ratio by capacity: 1.0		
Pot Life (24°C)	60	min	
Thermoset Mix Viscosity	2000	cP	
Additional Information	Nominal Value	Unit	
Cured 7 days @ 75°F			
Uncured Properties	Nominal Value	Unit	
Curing Time	24	hr	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

