

Sinvicomp SFC8210

Flexible Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp SFC8210 is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific for injection molding.
Typical application of Sinvicomp SFC8210: Consumer Goods

General Information			
Features	Foamable		
Uses	Footwear		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness	56		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	12.2	MPa	ASTM D638
Tensile Elongation (Break)	380	%	ASTM D638
Thermal	Nominal Value		Test Method
Heat Stability ¹ (190°C)	65.0		BS 2782
NOTE			
1.	Congo Red		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT