

# EPAMOULD 660D12

Thermoplastic Polyurethane Elastomer (Polyester)

Epaflex Polyurethanes S.R.L.

## Message:

The EPAMOULD 600 series was created to meet the most stringent performance requirements in the footwear industry. Over time it has evolved to include the existing range of products, all made from polyester, which comprises:  
a series of products plasticized, phthalate-free and high fluidity  
a number of products to be free from plasticizers, robust and suitable to the technical sector.

| General Information          |                   |                   |
|------------------------------|-------------------|-------------------|
| Additive                     | Beeswax           |                   |
| Uses                         | Footwear          |                   |
| Appearance                   | Clear/transparent |                   |
| Processing Method            | Injection molding |                   |
| Physical                     | Nominal Value     | Unit              |
| Density                      | 1.20              | g/cm <sup>3</sup> |
| Hardness                     | Nominal Value     | Unit              |
| Durometer Hardness (Shore D) | 60                |                   |
| Mechanical                   | Nominal Value     | Unit              |
| Abrasion Loss                | 45.0              | mm <sup>3</sup>   |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

