POLYTROPE® STR 3571EU-01 NATURAL

Enhanced Polyolefin (Capstock Resin)

A. Schulman Inc.

Message:

POLYTROPE STR 3571EU resin is an ultra-low gloss, weatherable, olefin cap resin. It is resistant to stress whitening and provides exceptional durability against denting and scratches. It is specifically designed for the co-extrusion process as a cap resin over POLYTROPE STR enhanced polyolefin TPO and FR TPO base resins. It is especially suited for thermoformed applications, as it maintains embossed texture and ultra-low gloss through the thermoforming process. POLYTROPE STR 3571EU-01 NATURAL is easily colored. The ultra-low gloss and durability of the cap resin enables it to match or exceed the performance and appearance of other ultra-low gloss surfacing materials for interior and exterior applications.

| General Information | | | |
|--|-----------------------------------|----------|-------------|
| Features | Durable | | |
| | Good Chemical Resistance | | |
| | Good Weather Resistance | | |
| | High Scratch Resistance | | |
| | Low Temperature Impact Resistance | | |
| | Recyclable Material | | |
| | Stain Resistant | | |
| | Stress Whitening Resistant | | |
| | | | |
| Forms | Pellets | | |
| Processing Method | Coextrusion | | |
| | Extrusion | | |
| | Profile Extrusion | | |
| | Sheet Extrusion | | |
| | Thermoforming | | |
| | | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity ¹ | 0.928 | g/cm³ | ISO 1183 |
| Melt Mass-Flow Rate (MFR) (230°C/2.16 | | | |
| kg) | 4.5 | g/10 min | ISO 1133 |
| Optical | Nominal Value | | Test Method |
| Gardner Gloss (60°, Thermoformed, Smooth) | < 20 | | ISO 2813 |
| NOTE | | | |
| 1. | Method A | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

