

MACOMASS PVC MM-PVC E 1595

Flexible Polyvinyl Chloride

MACOMASS Verkaufs AG

Message:

MACOMASS PVC MM-PVC E 1595 is a flexible polyvinyl chloride material. This product is available in Europe and is processed by extrusion.

The main characteristics of MACOMASS PVC MM-PVC E 1595 are:

Stable
plasticization

General Information			
Additive	Tin stabilizer		
	Plasticizer		
Features	Low (to no) lead content		
	Calcium content, low (to none)		
Appearance	Clear/transparent		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.26 - 1.30	g/cm ³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ISO 868
Shao A, 3 seconds	92 - 98		ISO 868
Shaw D, 3 seconds	47 - 57		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	> 22.0	MPa	ISO 527-2
Elastomers	Nominal Value	Unit	Test Method
Tensile Elongation (Break)	> 300	%	ISO 37
Extrusion	Nominal Value	Unit	
Melt Temperature	135 - 170	°C	
Extrusion instructions			
Compression: 2:1 or 2.5:1Screw Length: >20 d			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

