

# T-Blend® 7594N-PE-T

Styrene Ethylene Butylene Styrene Block Copolymer

TSRC Corporation

Message:

T-Blend® 7594N-PE-T is a Styrene Ethylene Butylene Styrene Block Copolymer (SEBS) product. It is available in Asia Pacific. Applications of T-Blend® 7594N-PE-T include wire & cable and engineering/industrial parts.

Characteristics include:

- RoHS Compliant
- WEEE Compliant
- Eco-Friendly/Green
- Flame Retardant
- Good Aesthetics

General Information			
Features	Flame Retardant		
	Good Processability		
	Good Surface Finish		
	Halogen Free		
	High Heat Resistance		
	Low Smoke Emission		
	Non-Toxic		
	Recyclable Material		
	Soft		
Uses	Plugs		
	Wire & Cable Applications		
Agency Ratings	EU 2002/96/EC (WEEE)		
	UL Unspecified Rating		
RoHS Compliance	RoHS Compliant		
Appearance	Natural Color		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.870 to 0.910	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (180°C/5.0 kg)	1.3	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	73 to 77		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Break)	7.85	MPa	ASTM D412
Tensile Elongation (Break)	660	%	ASTM D412
Tear Strength	47.1	kN/m	ASTM D624
Injection	Nominal Value	Unit	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

