

# Jam PE 534F7

High Density Polyethylene  
Jam Petrochemical Company

Message:

Jam PE 534F7 is a High Density Polyethylene product. It is available in Africa & Middle East. Typical application: Fabrics/Fibers.

General Information			
Features	Med.-Wide Molecular Weight Distrib.		
Uses	Monofilaments		
Physical	Nominal Value	Unit	Test Method
Density	0.953	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.70	g/10 min	ASTM D1238
Flow Rate Ratio	40.0		ASTM D1238
Fish Eye	50.0	No./m <sup>2</sup>	
Titanium	5	ppm	
Films	Nominal Value	Unit	
Film Thickness - Tested	25	µm	
Optical	Nominal Value	Unit	Test Method
Yellowness Index	1.0	YI	ASTM D1925

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT