

PrimaFlex® HD 5320

High Density Polyethylene
Plastic Solutions, Inc.

Message:

Description: HD 5320 is a copolymer with good processability and excellent balance of ESCR, toughness and stiffness properties.

General Information	
Features	Balanced Stiffness/Toughness Copolymer Good Processability Good Stiffness Good Toughness High ESCR (Stress Crack Resist.) Low Warpage
Uses	Appliances Consumer Applications General Purpose Housings Toys White Goods & Small Appliances

Physical	Nominal Value	Unit	Test Method
Density	0.953	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	20	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	65		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	24.1	MPa	ASTM D638
Flexural Modulus	1280	MPa	ASTM D790
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	< -75.0	°C	ASTM D746

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

