

HIFOR® LT74119

Linear Low Density Polyethylene

Westlake Chemical Corporation

Message:

WESTLAKE HIFOR Polyethylene LT74119 is a high strength linear low density polyethylene containing medium slip and high antiblock and it contains processing aid. It is designed for blown applications and is well suited for consumer and industrial packaging markets which require impact and tear strength. Films produced using LT74119 exhibit low imperfections and facilitate production at thinner gauges.

General Information			
Additive	Medium Antiblock		
	Medium Slip		
	Processing Aid		
Features	Good Impact Resistance		
	Good Tear Strength		
	High Strength		
	Medium Antiblocking		
	Medium Slip		
Uses	Film		
	Food Packaging		
	Packaging		
Agency Ratings	FDA 21 CFR 177.1520		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ASTM D4883
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Secant Modulus			ASTM D882
1% Secant, MD	220	MPa	
1% Secant, TD	241	MPa	
Tensile Strength			ASTM D882
MD : Break	50.0	MPa	
TD : Break	39.0	MPa	
Tensile Elongation			ASTM D882
MD : Break	750	%	
TD : Break	1000	%	
Dart Drop Impact	170	g	ASTM D1709
Optical	Nominal Value	Unit	Test Method

Gloss (45°)	45		ASTM D2457
Haze	14	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

