

Durez® 32275

Phenolic

Sumitomo Bakelite North America, Inc.

Message:

Durez 32275 is a finely pulverized two-step thermosetting phenolic resin.

Durez 32275 resin is used to impart reinforcement to NBR stocks used in tape manufacture.

General Information			
Uses	Blending		
Thermal	Nominal Value	Unit	Test Method
Softening Point ¹	94	°C	Internal Method
Hexa	7.3	%	Internal Method
Inclined Plate Flow (125°C)	2.10	cm	Internal Method
Screen Mesh ²	< 0.25	%	Internal Method
Thermoset	Nominal Value	Unit	Test Method
Post Cure Time (165°C)	6.7E-3	hr	
NOTE			
1.	cap. shrink		
2.	200 Mesh		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

