Shanghai Potomer SG1

Flexible Polyvinyl Chloride

Shanghai Potomer International Trade Co., Ltd.

Message:

PVC suspension Resin is Calcium Carbide base, mainly used as sheet, pipe, window profiles and other molded parts. APPLICATIONS: cable sheathing and insulation, flexible films and sheets, water proof membranes, Flexible profiles

General Information			
Features	Good Flexibility		
Uses	Cable Jacketing		
	Film		
	Insulation		
	Membranes		
	Profiles		
	Sheet		
Processing Method	Calendering		
	Extrusion		
Physical	Nominal Value	Unit	
Apparent Density	> 0.45	g/cm³	
K (wear) Factor	75.0 to 77.0		
Sieve Analysis			
0.063mm sieve	> 90	%	
0.25mm sieve	< 2.0	%	
Viscosity	144 to 156	cm³/g	
Volatile Matter	< 0.30	%	
Conductivity	< 0.00500	S/m	
Fish Eye	< 20.0	pcs/400 cm²	
Impurities	< 16.0	pcs	
Whiteness - after 10min (160°C)	> 74	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

