

Sylvin 8749-80UV Natural

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:

Sylvin 8749-80UV Natural Is A Vinyl Compound Formulated For Profile Extrusion Applications This Compound Contains A Ultra Violet Stabilizer And A Anti-Oxidant.

General Information	
Additive	Antioxidation UV stabilizer
Features	Antioxidation General
Uses	Industrial application General Profile
Appearance	Natural color
Processing Method	Extrusion Profile extrusion molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.34	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	80		ASTM D2240
Shaw A, 10 seconds	80		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	15.9	MPa	ASTM D638
Tensile Elongation (Break)	370	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	59.5	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	166 - 177	°C	
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	24	%	ASTM D2863

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHEG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT