

# Trademark PP PPH1200MA

Polypropylene Homopolymer  
Trademark Plastics Corporation

Message:

Trademark PP PPH1200MA is a Polypropylene Homopolymer (PP Homopolymer) product. It can be processed by injection molding and is available in North America. Applications of Trademark PP PPH1200MA include caps/lids/closures, containers, food contact applications, kitchenware and packaging. Characteristics include:

- Low to No Odor/Taste
- Antistatic
- Food Contact Acceptable
- Good Processability
- Homopolymer

General Information			
Additive	Antistatic		
	Nucleating Agent		
Features	Antistatic		
	Food Contact Acceptable		
	Good Color Stability		
	Good Flow		
	Good Processability		
	Homopolymer		
	Low to No Odor		
	Low to No Taste		
	Nucleated		
Uses	Closures		
	Rigid Packaging		
	Table Products		
	Thin-walled Containers		
Agency Ratings	FDA 21 CFR 177.1520		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	12	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength <sup>1</sup> (Yield)	39.3	MPa	ASTM D638
Tensile Elongation <sup>2</sup> (Yield)	8.0	%	ASTM D638
Flexural Modulus	1930	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method

Notched Izod Impact (23°C)	37	J/m	ASTM D256
NOTE			
1.	50 mm/min		
2.	51 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

