

BorSafe™ ME3445

Medium Density Polyethylene

Borealis AG

Message:

BorSafe ME3445 is a bimodal polyethylene compound produced by the advanced Borstar technology.

It's fully stabilized against thermal degradation and the die build-up during extrusion is minimized. Furthermore, it has a highly covered pigment that gives a bright colored stripe even when extruded as a thin layer on a black pipe. It also contains UV-stabilizer.

BorSafe ME3445 recommended for the production of identifying stripes of black pipes produced from BorSafe ME3440.

General Information			
Additive	Unspecified Stabilizer		
	UV Stabilizer		
Features	Good Color Stability		
	Good Thermal Aging Resistance		
	Good UV Resistance		
Uses	Piping		
Appearance	Blue		
Forms	Pellets		
Processing Method	Coextrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.943	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	0.85	g/10 min	ISO 1133

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

