

DENKA EVA TEX 55N

Ethylene Vinyl Acetate Copolymer

Denka Company Limited

Message:

DENKA EVA TEX 55N is an Ethylene Vinyl Acetate Copolymer (EVA) product. It is available in Asia Pacific, Europe, or North America. Typical application: Adhesives/Tapes.

General Information			
Uses		Adhesives Paint	
Physical	Nominal Value	Unit	Test Method
Particle Size	500	nm	Internal Method
pH	4.5 to 6.0		
Solids Content	54 to 56	%	
Viscosity ¹ (30°C)	1.00 to 5.00	Pa·s	Brookfield
Minimum Film-forming Temperature	< 0	°C	
Films	Nominal Value	Unit	Test Method
Tensile Strength - MD (Yield)	2.50	MPa	ASTM D882
Tensile Elongation - MD (Break)	800	%	ASTM D882
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	-10.0	°C	ASTM E1356
NOTE			

1.

Brookfield viscometer, BM model,
30rpm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

