

Moplen EP2596

Polypropylene Impact Copolymer

LyondellBasell Industries

Message:

Moplen EP2596 is a nucleated polypropylene impact copolymer, suitable for injection moulding applications and contains antistatic agent. This grade exhibits good stiffness with medium fluidity.
Potential applications include houseware, furniture, pails, cylindrical containers and crates.

General Information			
Additive	Nucleating agent		
	Antistatic property		
Features	Nucleated		
	Rigid, good		
	Impact copolymer		
	Antistatic property		
	Medium liquidity		
Uses	Furniture		
	Household goods		
	Container		
	Loading box		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	20	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	28.0	MPa	ISO 527-2
Tensile Strain (Yield)	5.0	%	ISO 527-2
Flexural Modulus	1450	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	9.0	kJ/m ²	ISO 179

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

