McCann PP M40THPP10

Polypropylene Homopolymer

McCann Plastics Inc.

Message:

Excellent Heat Deflection Properties.

Talc Filled 40%, Polypropylene Homopolymer / Lawn & Garden, Industrial, Automotive, and general purpose applications requiring excellent stiffness and good flow. Custom color and UV stabilized versions also available.

General Information					
Filler / Reinforcement	Talc,40% Filler by Weight				
Features	General Purpose				
	Good Flow				
	Good Stiffness				
	Homopolymer				
	Medium Heat Resistance				
Uses	Automotive Applications				
	General Purpose				
	Industrial Applications				
	Lawn and Garden Equipment				
Appearance	Black				
	Colors Available				
	Natural Color				
Forms	Pellets				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.25	g/cm³	ASTM D792		
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	10	g/10 min	ASTM D1238		
Molding Shrinkage - Flow	1.1 to 1.5	%	ASTM D955		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	92		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength	31.7	MPa	ASTM D638		
Tensile Elongation (Break)	4.0	%	ASTM D638		
Flexural Modulus - Tangent	3520	МРа	ASTM D790		
Flexural Strength	54.5	МРа	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (23°C)	32	J/m	ASTM D256		
Gardner Impact	0.678	J	ASTM D3029		

Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			ASTM D648
0.45 MPa, Unannealed	143	°C	
1.8 MPa, Unannealed	87.8	°C	
Flammability	Nominal Value		Test Method
Flame Rating	НВ		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

