

NEOFLON™ AP-211SH

Perfluoroalkoxy

DAIKIN AMERICA, INC.

Message:

NEOFLON PFA is a copolymer of tetrafluoroethylene and perfluoroalkyl vinyl ether. It is a perfluoro polymer consisting of only carbon atoms and fluorine atoms without any hydrogen atom. It has the same excellent performance as PTFE in a wide range from extremely low to high temperatures. In addition, it has excellent transparency, mechanical strength at high temperature. It can be molded in the same molding method as general thermoplastic resins.

Features

High purity grade. Long-term flexibility and good stress crack resistance. Suitable for joints and parts for pumps.

General Information		
Features	High purity	
	High ESCR (Stress Cracking Resistance)	
	High temperature strength	
	Copolymer	
	Definition, high	
Uses	Pump parts	
Appearance	Clear/transparent	
Physical	Nominal Value	Unit
Melt Mass-Flow Rate (MFR)	10 - 17	g/10 min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT