YUPLENE® BH3820

Polypropylene Impact Copolymer

SK Global Chemical

Message:

23°C

Aging

YUPLENE BH3820 is an ultra high impact propylene copolymer designed for injection molding and compounding applications. YUPLENE BH3820 has excellent properties in impact strength as well as stiffness, flow, mechanical properties and heat resistance, which make YUPLENE BH3820 suitable for auto parts, electric appliances, large size containers, thin wall and very high speed injection applications.

General Information					
Features	Good Flow				
	Good Stiffness				
	High Heat Resistance				
	Impact Copolymer				
	Ultra High Impact Resistance				
Uses	Appliances				
	Automotive Applications				
	Compounding				
	Containers				
	Electrical/Electronic Applications				
	Industrial Applications				
	Thin-walled Parts				
Processing Method	Compounding				
	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Melt Mass-Flow Rate (MFR) (230°C/2.16					
kg)	28	g/10 min	ASTM D1238		
Spiral Flow	> 80.0	cm	Internal Method		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	72		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield)	20.6	MPa	ASTM D638		
Tensile Elongation (Break)	< 300	%	ASTM D638		
Flexural Modulus	981	МРа	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact			ASTM D256		
-20°C	69	J/m			

J/m

Unit

Test Method

> 490

Nominal Value

Accelerated Oven Aging - in Air (150°C)	15.0	day	ASTM D3012
Heat Deflection Temperature	110	°C	ASTM D648
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	150	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

