

MIDILENA III HDPE2200J

High Density Polyethylene

ROMPETROL PETROCHEMICALS S.R.L.

Message:

MIDILENA III HDPE2200J is a High Density Polyethylene product. It can be processed by injection molding and is available in Europe. Applications of MIDILENA III HDPE2200J include automotive and containers. Primary characteristic: antioxidant.

General Information			
Additive	Antioxidant		
	Halogen		
Features	Antioxidant		
	Halogenated		
Uses	Automotive Applications		
	Crates		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.960	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	5.0	g/10 min	ISO 1133

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT