

HIVOREX BL5200

High Density Polyethylene

Lotte Chemical Corporation

Message:

HIVOREX BL5200 is produced by slurry process technology.

This resin is ideally suited for use in blow molding application.

HIVOREX BL5200 is designed to offer high stiffness, excellent impact resistance, good resistance at low temp and chemicals resistance.

General Information			
Features	Good Chemical Resistance		
	Good Impact Resistance		
	High Stiffness		
	Low Temperature Resistant		
Uses	Blow Molding Applications		
	Bottles		
	Toys		
Processing Method	Blow Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.964	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.30	g/10 min	ASTM D1238
Environmental Stress-Cracking Resistance (F50)	30.0	hr	ASTM D1693
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	28.4	MPa	ASTM D638
Tensile Elongation (Break)	> 500	%	ASTM D638
Flexural Modulus	1270	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	540	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	< -80.0	°C	ASTM D746
Vicat Softening Temperature	125	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

