

MIDILENA I LDPE B22/0.7

Low Density Polyethylene

ROMPETROL PETROCHEMICALS S.R.L.

Message:

MIDILENA I LDPE B22/0.7 is a Low Density Polyethylene product. It can be processed by blown film or extrusion and is available in Europe. Applications of MIDILENA I LDPE B22/0.7 include agricultural and film. Primary characteristic: antioxidant.

General Information	
Additive	Antioxidant
Features	Antioxidant
Uses	Agricultural Applications
	Film
Forms	Pellets
Processing Method	Blown Film
	Extrusion

Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.70	g/10 min	ISO 1133

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT