

# SolVin 367NF

Polyvinyl Chloride  
INOVYN

Message:

Polyvinyl chloride made by microsuspension polymerisation for plastisol preparation.

MAIN APPLICATIONS

- Spread coating :  
artificial leather compact layer  
artificial leather foam layer  
flooring foam layer  
flooring impregnation layer  
flooring backing foam  
wall covering compact layer.  
Moulding and dipping.

ADVANTAGES

- High filler acceptance.  
Not sticking over a wide temperature range on a pregelation drum.

General Information			
Uses	Coating Applications		
	Flooring		
	Foam		
	Synthetic Leather		
	Wall Panels		
Processing Method		Plastisol	
Physical	Nominal Value	Unit	Test Method
K-Value	67.0		ISO 1628-2
Sieve Analysis - Retained on 0.125 mm sieve	< 0.200	g/kg	ISO 787-18
Volatile Matter	< 0.30	%	ISO 1269

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT