

Karina MBPEB WHITE 1000/5035-IE

Polyvinyl Chloride

Karina Ind. e Com. de Plásticos Ltda

Message:

MASTERBATCH WITH 50% OF TIO2 - USAGE FROM 1 TO 5% DEPENDING ON THE CLIENT NEED AND NECESSITY OF COVERING.

General Information			
Additive	Titanium Dioxide (TiO2) (50%)		
Uses	Masterbatch		
Appearance	White		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.40 to 2.46	g/cm ³	ASTM D792
Ash Content - CaCO ₃	83 to 87	%	ME 51
Color	OK		ME 12
Dispersion	OK		ME 56
Granulometry	20.0 to 30.0	pellets/g	ME 05
Heat Resistance	300	°C	DIN 53772
Light-Fastness	8.00		DIN 53388
Masterbatch Moisture	< 0.10	%	ME 52
Migration Resistance	5.00		DIN 53775

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

