

STARFLEX® P 7002

Thermoplastic Elastomer

STAR Thermoplastic Alloys & Rubbers, Inc.

Message:

STARFLEX® P 7002 is a Thermoplastic Elastomer (TPE) material. It is available in North America for extrusion or injection molding. Primary attribute of STARFLEX® P 7002: Good Weather Resistance.

General Information	
Features	Good Weather Resistance
Appearance	Translucent
Forms	Pellets
Processing Method	Extrusion Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.900	g/cm ³	ASTM D792
Molding Shrinkage - Flow	3.2 to 4.2	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	2		ASTM D2240

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

