

Hostacom CR 1171 G

Polypropylene Impact Copolymer

LyondellBasell Industries

Message:

"Hostacom" CR 1171 G is a medium melt flow rate, high impact polypropylene copolymer designed for injection moulding. It features a long term UV resistance.
This grade is available in custom color, pellet form.

General Information			
Additive	UV Stabilizer		
Features	Good UV Resistance		
	High Impact Resistance		
	Impact Copolymer		
	Medium Flow		
	Non-Toxic		
Uses	Automotive Applications		
	Automotive Instrument Panel		
	Automotive Interior Parts		
Appearance	Colors Available		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.990	g/cm ³	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	11	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	1800	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength			ISO 180/1A
-30°C	6.0	kJ/m ²	
23°C	30	kJ/m ²	
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	54.0	°C	ISO 75-2/A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

