

Shandong Aobang TPU-Polyester 95-A

Thermoplastic Polyurethane Elastomer (Polyester)

Shandong Aobang Chemical Technology Co.,Ltd.

Message:

Shandong Aobang TPU-Polyester 95-A is a Thermoplastic Polyurethane Elastomer (Polyester) (TPU-Polyester) product. It is available in Asia Pacific. Applications of Shandong Aobang TPU-Polyester 95-A include additive/masterbatch, industrial applications and sealing applications.

General Information			
Uses	Blending		
	Industrial Applications		
	Plastics Modification		
	Seals		
	Wheels		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore A)	93 to 97		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress			ASTM D412
100% Strain	> 14.0	MPa	
300% Strain	> 28.0	MPa	
Tensile Strength (Break)	> 40.0	MPa	ASTM D412
Tensile Elongation (Break)	> 380	%	ASTM D412
Tear Strength	> 140	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	-30.0	°C	DSC
Service Temperature	195 to 215	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT