

# KEP® 980

Ethylene Propylene Diene Terpolymer

Kumho Polychem Co., Ltd.

## Message:

### Features:

High mooney viscosity & high ethylene content, high filler loading, & good physical properties

### Applications:

Window seals, moldings in general, shock absorbing rubber(muffler hanger/engine mount), washing machine gasket, TPV

General Information		
Features	High Viscosity	
Uses	Appliance Components	
	Automotive Applications	
	Gaskets	
	Rubber Replacement	
	Seals	
Forms	Bale	
Processing Method	Injection Molding	
Physical	Nominal Value	Unit
Mooney Viscosity (ML 1+8, 125°C)	58	MU
Ethylene Content	71.0	wt%
Ethylidene Norbornene (ENB) Content	4.5	wt%
Oil Type (Unspecified Oil)	75.0	phr

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

