DOW™ HDPE NG7005

High Density Polyethylene Resin

The Dow Chemical Company

Message:

HDPE NG 7005 is a High Density Polyethylene Resin designed for thin gauge films. This resin offers high melt strength and bubble stability along with good mechanical properties. Main Characteristics: Complies with Regulation U.S. FDA 21 CFR 177.1520(c)3.2a Complies with European Commission Regulation (EU) No 10/2011 Consult the regulation for complete details

General Information			
Agency Ratings	EU No 10/2011		
	FDA 21 CFR 177.1520(c) 3.2a		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.945	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR)			ASTM D1238
190°C/2.16 kg	0.22	g/10 min	
190°C/21.6 kg	7.2	g/10 min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

