

# SoundX SoundX

Unspecified  
Spartech Plastics

Message:

Manufactured from a blend of specialized materials, this alloy offers sound abatement properties for both the automotive and construction markets. Placing SoundX between walls of buildings or indoor panels of automobiles significantly reduces noise levels and also serves as a moisture barrier.

General Information			
Features	Moisture proof		
	Noise reduction		
Uses	Architectural application field		
	Application in Automobile Field		
Forms	Sheet		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.00	g/cm <sup>3</sup>	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	24.1	MPa	ASTM D638
Tensile Elongation (Break)	550	%	ASTM D638
Flexural Strength	44.8	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT