

# Karina CLEAR PVC COMPOUND -E

## 75/218-D-IS-AS

Polyvinyl Chloride

Karina Ind. e Com. de Plásticos Ltda

Message:

UV RESISTANT PVC COMPOUND RECOMMENDED FOR HOSES AND PROFILES EXTRUSION.

General Information			
Features	Good UV Resistance		
Uses	Hose		
	Profiles		
Appearance	Clear/Transparent		
Processing Method	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Density <sup>1</sup>	1.20 to 1.26	g/cm <sup>3</sup>	IEC 60811-1-3
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	73 to 77		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress	> 13.7	MPa	IEC 60811-1-1
Tensile Strain (Yield)	> 250	%	IEC 60811-1-1
Additional Information	Nominal Value		Test Method
Clearness	OK		ME 03
NOTE			
1.	24 hr		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT