

# Fixmaster Steel Stick

Epoxy; Epoxide

Loctite®

## Message:

Fixmaster Steel Stick is an Epoxy; Epoxide (Epoxy) product filled with steel. It is available in North America. Applications of Fixmaster Steel Stick include industrial applications and repairing material. Primary characteristic: chemical resistant.

General Information			
Filler / Reinforcement	Steel		
Features	Fast Cure		
	Good Chemical Resistance		
	Underwater Curable		
Uses	Industrial Applications		
	Metal Repairing Material		
Appearance	Grey		
Forms	Pellets		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore D)	80		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	17.2	MPa	ASTM D638
Compressive Strength	42.7	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	93.3	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Pot Life (25°C)	3.0	min	
Demold Time (25°C)	10	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT